

CENTER 300/301/302/303 Thermometer (K Type, K J Type) (เครื่องวัดค่าอุณหภูมิ)



FEATURES

- Timer Function (300, 302)
- Dual Input (301, 303)
- Dual Display (301, 303)
- PC Interface
- Auto Power Off
- Resolution 0.1°C, 0.1°F

SPECIFICATIONS

Range	K type: -200 ~ 1370 °C, -328 ~ 2498 °F (300 ~ 303) J type: -200 ~ 760 °C, -328 ~ 1400 °F (302 ~ 303)
Accuracy	±0.1%+0.7 °C, ±0.1%+1.4 °F
Resolution	0.1 °C, 0.1 °F
Operation Temp.	0 °C ~ 50 °C (<80%RH)
Storage temp.	-20 °C ~ 60 °C (<70%RH)
Battery	9V Battery
Dimensions	184 x 64 x 30 mm
Weight	Approx. 210g.

STANDARD ACCESSORIES

MODEL	Battery	Manual	Carrying case	K-Type bead sensor	RS-232 cable	Software
CENTER 300	•	•	•	TP-K01 x 1 PC	Option	Option
CENTER 301	•	•	•	TP-K01 x 2 PCS		
CENTER 302	•	•	•	TP-K01 x 1 PC		
CENTER 303	•	•	•	TP-K01 x 2 PCS		

300 K Type

301 K Type Dual Input

302 K J Type

303 K J Type Dual Input

CENTER 307/308 Thermometer (K Type, Compact Size, Low Cost) (เครื่องวัดค่าอุณหภูมิ)



FEATURES

- Mini Size
- Dual Input (308)
- Dual Display (308)
- Auto Power Off
- Resolution 0.1°C, 0.1°F

SPECIFICATIONS

Range	-200 ~ 1370 °C, -328 ~ 2498 °F
Accuracy	±0.3%+1 °C, ±0.3%+2 °F
Resolution	0.1 °C, 0.1 °F
Input Protection	60VDC or 24Vrms AC Maximum
Operation Temp.	0 °C ~ 40 °C (<80%RH)
Storage temp.	-10 °C ~ 60 °C (<70%RH)
Battery	9V Battery
Dimensions	164 x 54 x 34 mm
Weight	Approx. 200g.

STANDARD ACCESSORIES

MODEL	Battery	Manual	K-Type bead sensor
CENTER 307	•	•	TP-K01 x 1 PC
CENTER 308	•	•	TP-K01 x 2 PCS

307 K Type

308 K Type Dual Input

CENTER 304 Thermometer (K Type, 4 Channels Input) (เครื่องวัดค่าอุณหภูมิแบบ 4 Channels)



FEATURES

- Auto Power Off
- Four Channel Input
- Four Channel Display
- Wide Measuring Range
- PC Interface
- Resolution 0.1°C, 0.1°F

SPECIFICATIONS

Range	K Type:-200 ~ 1370 °C, -328 ~ 2498 °F
Accuracy	±0.3%+1 °C, ±0.3%+2 °F
Resolution	0.1 °C, 0.1 °F
Input Protection	60V DC or 24 Vrms AC Maximum
Operation Temp.	0 °C ~ 50 °C (<80%RH)
Storage temp.	-20 °C ~ 60 °C (<70%RH)
Battery	9V Battery
Dimensions	184 x 64 x 30 mm
Weight	Approx. 220g.

STANDARD ACCESSORIES

MODEL	Battery	Manual	Carrying case	K-Type bead sensor	RS-232 cable	Software
CENTER 304	•	•	•	TP-K01 x 2 PCS	Option	Option



SE-300 RS-232
cable for PC interface (option),
Software SE 310 (option)