

CENTER 305/306

Thermometer (K Type, Datalogger, PC Interface) (เครื่องวัดค่าอุณหภูมิพร้อมเก็บข้อมูลในตัว)



FEATURES

- Dual Input (306)
- Triple Display
- Clock Function
- PC Interface
- With Windows Software
- 16,000 Records Datalogger
- Resolution 0.1 °C, 0.1 °F



305 K Type
306 K Type Dual Input

SPECIFICATIONS

Range	K type: -200 ~ 1370 °C, -328 ~ 2498 °F
Accuracy	±0.3%+1 °C, ±0.3%+2 °F
Resolution	0.1 °C, 0.1 °C
Operation Temp.	0 °C ~ 50 °C (<80%RH)
Storage temp.	-20 °C ~ 60 °C (<70%RH)
Battery	9V Battery
Dimensions	184 x 64 x 30 mm
Weight	Approx. 210g.

STANDARD ACCESSORIES

MODEL	Battery	Manual	Carrying case	K-Type bead sensor	RS-232 cable	Software
CENTER 305	•	•	•	TP-K01 x 1 PC	•	•
CENTER 306	•	•	•	TP-K01 x 2 PCS	•	•

CENTER 309

Thermometer (K Type, 4 Channels, Datalogger, PC Interface)
(เครื่องวัดค่าอุณหภูมิ 4 Channels พร้อมเก็บข้อมูลในตัว)



FEATURES

- Auto Power Off
- Four Channel Input
- Four Channel Display
- Wide Measuring Range
- With Windows Software
- PC Interface
- 16,000 Records Datalogger Each Channel
- Resolution 0.1 °C, 0.1 °F

SPECIFICATIONS

Range	K Type:-200 ~ 1370 °C, -328 ~ 2498 °F
Accuracy	±0.3%+1 °C, ±0.3%+2 °F
Resolution	0.1 °C, 0.1 °F
Input Protection	60V DC or 24 Vrms AC Maximum
Operation Temp.	0 °C ~ 50 °C (<80%RH)
Storage temp.	-20 °C ~ 60 °C (<70%RH)
Battery	9V Battery
Dimensions	184 x 64 x 30 mm
Weight	Approx. 220g.

STANDARD ACCESSORIES

MODEL	Battery	Manual	Carrying case	K-Type bead sensor	RS-232 cable	Software
CENTER 309	•	•	•	TP-K01 x 2 PCS	•	•



CENTER 374

Thermometer (K Type, 4 Channels, Datalogger, PC Interface)
(เครื่องวัดค่าอุณหภูมิ 4 Channels พร้อมเก็บข้อมูลในตัว)



FEATURES

- Auto Range
- PC Interface
- Hold Function
- Four Channel Input
- Four Channel Display
- Resolution 0.1 °C, 0.1 °F
- With Windows Software
- MAX/MIN/Avg Function
- Auto Shut Off for Battery Saving
- 16,000 Records Datalogger Each Channel

SPECIFICATIONS

Range	-200 ~ 1370 °C, -328 ~ 2498 °F
Accuracy	±0.3%+1 °C, ±0.3%+2 °F
Resolution	0.1 °C, 0.1 °F
Input Protection	60V DC or 24 Vrms AC Maximum
Operation Temp.	0 °C ~ 50 °C (<80%RH)
Storage temp.	-20 °C ~ 60 °C (<70%RH)
Battery	9V Battery
Dimensions	196 x 65 x 36 mm
Weight	Approx. 285g.

STANDARD ACCESSORIES

9V Battery, Operation Manual, Carrying case, Temperature probe TP-K01 x 2 pcs, Software SE 374, USB Cable

