

**CENTER 370** RTD Thermometer (Water Proof) (เครื่องวัดค่าอุณหภูมิแบบ 1 Channel)



**FEATURES**

- IP 67 Water Proof Housing to work for almost all Kinds of Environments
- PT Temperature Sensor for less Environmental Dependent Reading
- Adapt for PT100, PT500 and PT1000 Sensors with  $\alpha$  Value of 3850
- MAX/MIN/Avg. Function
- LCD Back Light
- °C, °F Scale selectable and 0.1 °C, 0.1 °F Resolution
- 3 Sectors Battery Life Indicator

**SPECIFICATIONS**

**CENTER 370/372**

|                      |                                                               |
|----------------------|---------------------------------------------------------------|
| Measurement Range    | -100 ~ 300 °C; -148 ~ 572 °F                                  |
| Measurement Accuracy | ±0.1%rdg ±0.4 °C                                              |
| Resolution           | 0.1 °C; 0.1 °F                                                |
| Sampling Rate        | 2 times/sec.                                                  |
| Water Resistance     | IP67 (EN60529:1991)                                           |
| Battery              | 1.5V, size AAA battery x3                                     |
| Dimensions           | 150 x 66 x 31mm                                               |
| Weight               | Approx. 175g.                                                 |
| Sensor Type          | Platinum temperature-measurement resistor (PT100/4 line type) |



WATER PROOF



LED Back Light



Included PT100 Probe (TP-R01 x 1pc.)

**STANDARD ACCESSORIES**

PT100 Probe (Class A) , Battery , Instruction Manual.

**CENTER 372** RTD Thermometer (Water Proof/Dual Input) (เครื่องวัดค่าอุณหภูมิแบบ 2 Channel)



**FEATURES**

- IP 67 Water Proof Housing to work for almost all Kinds of Environments
- PT Temperature Sensor for less Environmental Dependent Reading
- PT100 Sensor with  $\alpha$  Value of 3850/3926/3916 RTD Standard
- MAX/MIN/Avg. Function
- LCD Back Light
- °C, °F Scale selectable and 0.1°C, 0.1 °F Resolution
- 3 Sectors Battery Life Indicator
- Dual Input Channels

**FUNCTION TABLE**

| MODEL               | CENTER 370 | CENTER 372 |
|---------------------|------------|------------|
| °C , °F Selectable  | •          | •          |
| Dual Display        | •          | •          |
| Dual Input Channels |            | •          |
| LCD Back Light      | •          | •          |
| Auto Power Off      | •          | •          |



WATER PROOF



LED Back Light

Included PT100 Probe (TP-R01 x 2pc.)

